

Application No.: 09/988,793

Docket No.: R2180.0113/P113

AMENDMENTS TO THE CLAIMS

1-3. (Canceled)

4. (Previously Presented) A camera apparatus comprising a zoom lens, said zoom

lens comprising:

a first lens band having a positive focal length;

a second lens band having a negative focal length;

at least third to fifth lens bands having positive focal lengths; and

an aperture diaphragm located in the vicinity of the third lens band;

wherein, said second lens band smoothly moves toward the third lens band and said fourth lens band moves from the fifth lens band side toward a long focal point end so as to share a magnifying function together with the second lens band, when magnification is performed from short to long focal point ends; and

wherein a distance (D1W) between the first and second lens bands in the short focal point end arrangement, a distance (D1T) between the first and second lens bands in the long focal point end arrangement, a distance (D3W) between the third and fourth lens bands in the short focal point end arrangement, and a distance (D3T) between the third and fourth lens bands in the long focal point end arrangement substantially meet the following inequality:

$$(D3W - D3T) / (D1T - D1W) > 0.3.$$

Application No.: 09/988,793

Docket No.: R2180.0113/P113

5. (Previously Presented) The apparatus according to claim 4 wherein the first lens band faces an object to be photographed.

6. (Previously Presented) The apparatus according to claim 4 wherein said fourth lens band comes closest to the third lens band at a focal length slightly before the long focal point end.

7. (Previously Presented) A camera apparatus comprising a zoom lens, said zoom

lens comprising:

a first lens band having a positive focal length;

a second lens band having a negative focal length;

at least third to fifth lens bands having positive focal lengths; and

an aperture diaphragm located in the vicinity of the third lens band;

wherein, said second lens band smoothly moves toward the third lens band and said fourth lens band moves from the fifth lens band side toward a long focal point end so as to share a magnifying function together with the second lens band, when magnification is performed from short to long focal point ends; and

wherein a variance of an image surface caused by the smooth movements of said second and fourth lens bands is compensated by movement of the fifth lens band in a predetermined direction.

8. (Original) The camera apparatus according to claim 7, wherein said first lens band is immobile.

Application No.: 09/988,793

Docket No.: R2180.0113/P113

9. (Original) The camera apparatus according to claim 7, wherein said third lens band and aperture diaphragm are immobile.

10. (Currently Amended) The camera apparatus according to claim 7, wherein the fifth lens band performs focussing focusing.

11. (Original) The camera apparatus according to claim 7, wherein a focal length ( $f_1$ ) of the first lens band, and a composite focal length ( $f_{12T}$ ) of the first and second lens bands at the long focal point end substantially meet the following inequality:

$$-1.4 < (f_{12T} / f_1) < -1.0$$

12. (Original) The camera apparatus according to claim 7, wherein a composite focal length ( $f_{12W}$ ) of the first and second lens bands at the short focal point end, a composite focal length ( $f_{12T}$ ) of the first and second lens bands at the long focal point end, a focal length ( $f_T$ ) of the entire lens unit at the long focal point end, and a focal length ( $f_W$ ) of the entire lens unit at the short focal point end substantially meet the following inequality:

$$0.4 < (f_{12T} / f_{12W}) / (f_T / f_W) < 0.7$$

13. (Original) The camera apparatus according to claim 7, wherein each of said lens bands includes less than three lenses, said second and third lens bands include at least one non-spherical surface, and at least one of said fourth and fifth lens band includes more than one non-spherical surfaces.

14. (Currently Amended) The camera apparatus according to claim 7, wherein said first to third and fifth lens bands include less than three lenses, said fourth lens band includes four lenses, each of said second and third lens bands includes

Application No.: 09/988,793

Docket No.: R2180.0113/P113

at least one non-spherical surface, and at least one of said fourth and fifth lens band includes more than one non-spherical surfaces.

15. (Original) The camera apparatus according to claim 7, wherein said fifth lens band includes only one lens.

16. (Original) The camera apparatus according to claim 7, wherein said aperture diaphragm is located at the object side of the third lens band.

17. (Original) The camera apparatus according to claim 7, further comprising a function of digitizing a photographed image into digital information.

18. (Original) The camera apparatus according to claim 17, further comprising a photo acceptance unit configured to receive an image from the zoom lens, said photo acceptance unit having almost three millions of pixels.

19. (Original) The camera apparatus claimed in any one of claims 1, and 4 to 15, said zoom lens further comprising a macro mode capable of focusing at a shorter distance than an ordinal photographing region, wherein said focusing is performed by movement of the fifth lens band in a predetermined direction in any one of the ordinal photographing region and the macro mode.

20. (Original) The camera apparatus according to claim 19, wherein said fourth lens band in the macro mode is substantially close to the fourth lens band in the long focal point end arrangement.

21. (Original) The camera apparatus according to claim 19, wherein said second lens band in the macro mode is substantially closer to the image surface than when it is in the short focal point end arrangement.

Application No.: 09/988,793

Docket No.: R2180.0113/P113

22. (Original) The camera apparatus according to claim 19, wherein said fourth lens band in the macro mode is close to the fourth lens band in the long focal point end arrangement, and wherein said second lens band in the macro mode is closer to the imaging surface than when it is in the short focal point end arrangement.

23. (Original) The camera apparatus according to claim 19, wherein the first and third lens bands and the aperture diaphragm are immobile with regard to the image surface.

24. (Original) The camera according to claim 19, wherein a distance ( $L_{1w}$ ) between the first and second lens bands in the short focal point end arrangement, a distance ( $L_{1T}$ ) between the first and second lens bands in the long focal point end arrangement, a distance ( $L_{1c}$ ) between the first and second lens bands in the macro mode substantially meet the following inequality:

$$0.15 < (L_{1c} - L_{1w}) / (L_{1T} - L_{1w}) < 0.40$$

25. (Original) The camera apparatus according to claim 19, wherein a distance ( $L_{2w}$ ) between the third and fourth lens bands in the short focal point end arrangement, a distance ( $L_{3T}$ ) between the third and fourth lens bands in the long focal point end arrangement, a distance ( $L_{3c}$ ) between the third and fourth lens bands in the macro mode substantially meet the following inequality:

$$0.25 < (L_{3c} - L_{2w}) / (L_{2w} - L_{3T}) < 0.50$$

26. (Original) The zoom lens according to claim 19, wherein a distance ( $L_{1w}$ ) between the first and second lens bands in the short focal point end arrangement, a distance ( $L_{1T}$ ) between the first and second lens bands in the long focal point end

Application No.: 09/988,793

Docket No.: R2180.0113/P113

arrangement, a distance ( $L_{1c}$ ) between the first and second lens bands in the macro mode substantially meet the following inequality:

$$0.15 < (L_{1c} - L_{1w}) / (L_{1T} - L_{1w}) < 0.40$$

and wherein a distance ( $L_{2w}$ ) between the third and fourth lens bands in the short focal point end arrangement, a distance ( $L_{3T}$ ) between the third and fourth lens bands in the long focal point end, a distance ( $L_{3c}$ ) between the third and fourth lens bands in the macro mode substantially meet the following inequality:

$$0.25 < (L_{3c} - L_{2w}) / (L_{2w} - L_{3T}) < 0.50$$

27. (Currently Amended) The camera apparatus according to claim 19, wherein said first to third and fifth lens bands include less than three lenses, said fourth ~~lens~~ lens band includes four lenses, each of said second, third and fifth lens bands includes at least one non-spherical surfaces, and the fourth lens band includes more than two non-spherical surfaces.

28. (Original) The camera apparatus according to claim 19, wherein said third lens band includes one lens, and said aperture diaphragm is located at the object side of the third lens band.

29-30. (Canceled)

31. (Previously Presented) A method for zooming, comprising the steps of:  
providing a first lens band having a positive focal length;  
providing a second lens band having a negative focal length;  
providing at least third to fifth lens bands having positive focal lengths; and

Application No.: 09/988,793

Docket No.: R2180.0113/P113

providing an aperture diaphragm located in the vicinity of the third lens band;  
smoothly moving said second lens band toward the third lens band;  
substantially simultaneously moving said fourth lens band from the fifth lens  
band side toward a long focal point end so as to share a magnifying function together  
with the second lens band when magnification is performed from short to long focal  
point ends;

further comprising the step of compensating a variance of an image surface  
caused by the smooth movements of said second and fourth lens bands with movement  
of the fifth lens band in a predetermined direction.

32. (Previously Presented) The method according to claim 31, further  
comprising the step of fixing said first lens band when said magnification is performed.

33. (Canceled)

34. (Previously Presented) The method according to claim 31, further  
comprising the step of performing focusing with the fifth lens band when said  
magnification is performed.

35. (Canceled)

36. (Previously Presented) The method according to claim 31, further  
comprising

the step of focusing at a shorter distance than an ordinal photographing region  
by moving the fifth lens band in a predetermined direction in any one of the ordinal  
photographing region and the macro mode.

Application No.: 09/988,793

Docket No.: R2180.0113/P113

37. (Previously Presented) The method according to claim 31, further comprising the step of positioning said fourth lens band in a macro mode substantially close to the fourth lens band in the long focal point end arrangement for the macro mode.

38. (Previously Presented) The method according to claim 31, further comprising the step of positioning said second lens band substantially closer to the image surface than when it is in the short focal point end arrangement for the macro mode.

39-40. (Canceled)

41. (Previously Presented) A camera apparatus comprising zoom means for performing zooming, said zoom means comprising:

first means for deflecting a light, said first means having a positive focal length;  
second means for deflecting the light, said second means having a negative focal length;

at least third to fifth means for deflecting the lights, said at least third to fifth means having positive focal lengths; and

means for narrowing the light in the vicinity of the third means;

wherein, said second means smoothly move toward the third means and said fourth means move from the fifth means side toward a long focal point end so as to share a magnifying function together with the second means when magnification is performed from short to long focal point ends; and

Application No.: 09/988,793

Docket No.: R2180.0113/P113

wherein said fifth means perform focusing during zooming.

42. (Canceled)

43. (Previously Presented) A mobile information terminal, comprising a camera apparatus having a zoom lens, said zoom lens comprising:

a first lens band having a positive focal length;

a second lens band having a negative focal length;

at least third to fifth lens bands having positive focal lengths; and

an aperture diaphragm located in the vicinity of the third lens band;

wherein, said second lens band smoothly moves toward the third lens band and said fourth lens band moves from the fifth lens band side toward a long focal point end, when magnification is performed from short to long focal point ends; and

wherein a variance of an image surface caused by the smooth movements of said second and fourth lens bands is compensated by movement of the fifth lens band in a predetermined direction.

44. (Previously Presented) A zoom lens, comprising:

a first lens band having a positive focal length;

a second lens band having a negative focal length;

at least third to fifth lens bands having positive focal lengths; and

an aperture diaphragm located in the vicinity of the third lens band;

Application No.: 09/988,793

Docket No.: R2180.0113/P113

wherein, said second lens band smoothly moves toward the third lens band and said fourth lens band moves from the fifth lens band side toward a long focal point end, when magnification is performed from short to long focal point ends; and

wherein a variance of an image surface caused by the smooth movements of said second and fourth lens bands is compensated by movement of the fifth lens band in a predetermined direction.

45. (Previously Presented) The apparatus according to claim 43, wherein said first lens band is immobile.

46. (Previously Presented) The apparatus according to claim 43, wherein said third lens band and aperture diaphragm are immobile.

47. (Previously Presented) The apparatus according to claim 43, wherein the fifth lens band performs focusing.

48. (Previously Presented) The apparatus according to claim 43, wherein a focal length ( $f_1$ ) of the first lens band, and a composite focal length ( $f_{12T}$ ) of the first and second lens bands at the long focal point end substantially meet the following inequality:

$$-1.4 < (f_{12T} / f_1) < -1.0.$$

49. (Previously Presented) The apparatus according to claim 43, wherein a composite focal length ( $f_{12W}$ ) of the first and second lens bands at the short focal point end, a composite focal length ( $f_{12T}$ ) of the first and second lens bands at the long focal point end, a focal length ( $f_T$ ) of the entire lens unit at the long focal point end,

Application No.: 09/988,793

Docket No.: R2180.0113/P113

and a focal length ( $f_W$ ) of the entire lens unit at the short focal point end substantially meet the following inequality:

$$0.4 < (f_{12T} / f_{12W}) / (f_T / f_W) < 0.7.$$

50. (Previously Presented) The apparatus according to claim 43, wherein each of said lens bands includes less than three lenses, said second and third lens bands include at least one non-spherical surface, and at least one of said fourth and fifth lens band includes more than one non-spherical surface.

51. (Previously Presented) The apparatus according to claim 43, wherein said first to third and fifth lens bands include less than three lenses, said fourth lens band includes four lenses, each of said second and third lens bands includes at least one non-spherical surface, and at least one of said fourth and fifth lens band includes more than one non-spherical surface.

52. (Previously Presented) The apparatus according to claim 43, wherein said fifth lens band includes only one lens.

53. (Previously Presented) The apparatus according to claim 43, wherein said aperture diaphragm is located at the object side of the third lens band.

54. (Previously Presented) The apparatus according to claim 43, further comprising a function of digitizing a photographed image into digital information.

55. (Previously Presented) The apparatus according to claim 54, further comprising a photo acceptance unit configured to receive an image from the zoom lens, said photo acceptance unit having almost three million pixels.

Application No.: 09/988,793

Docket No.: R2180.0113/P113

56. (Previously Presented) The apparatus claimed in claim 52, said zoom lens further comprising a macro mode capable of focusing at a shorter distance than an ordinal photographing region, wherein said focusing is performed by movement of the fifth lens band in a predetermined direction in any one of the ordinal photographing region and the macro mode.

57. (Previously Presented) The apparatus according to claim 56, wherein said fourth lens band in the macro mode is substantially close to the fourth lens band in the long focal point end arrangement.

58. (Previously Presented) The apparatus according to claim 56, wherein said second lens band in the macro mode is substantially closer to the image surface than when it is in the short focal point end arrangement.

59. (Previously Presented) The apparatus according to claim 56, wherein said fourth lens band in the macro mode is close to the fourth lens band in the long focal point end arrangement, and wherein said second lens band in the macro mode is closer to the imaging surface than when it is in the short focal point end arrangement.

60. (Previously Presented) The apparatus according to claim 56, wherein the first and third lens bands and the aperture diaphragm are immobile with regard to the image surface.

61. (Previously Presented) The apparatus according to claim 56, wherein a distance (L1W) between the first and second lens bands in the short focal point end arrangement, a distance (L1T) between the first and second lens bands in the long focal point end arrangement, a distance (L1C) between the first and second lens bands in the macro mode substantially meet the following inequality:

Application No.: 09/988,793

Docket No.: R2180.0113/P113

$$0.15 < (L1C - L1W) / (L1T - L1W) < 0.40.$$

62. (Previously Presented) The apparatus according to claim 56, wherein a distance (L3W) between the third and fourth lens bands in the short focal point end arrangement, a distance (L3T) between the third and fourth lens bands in the long focal point end arrangement, a distance (L3C) between the third and fourth lens bands in the macro mode substantially meet the following inequality:

$$0.25 < (L3C - L3W) / (L3W - L3T) < 0.50.$$

63. (Previously Presented) The apparatus according to claim 56, wherein a distance (L1W) between the first and second lens bands in the short focal point end arrangement, a distance (L1T) between the first and second lens bands in the long focal point end arrangement, a distance (L1C) between the first and second lens bands in the macro mode substantially meet the following inequality:

$$0.15 < (L1C - L1W) / (L1T - L1W) < 0.40$$

and wherein a distance (L3W) between the third and fourth lens bands in the short focal point end arrangement, a distance (L3T) between the third and fourth lens bands in the long focal point end, a distance (L3C) between the third and fourth lens bands in the macro mode substantially meet the following inequality:

$$0.25 < (L3C - L3W) / (L3W - L3T) < 0.50.$$

64. (Previously Presented) The apparatus according to claim 56, wherein said first to third and fifth lens bands include less than three lenses, said fourth lens band includes four lenses, each of said second, third and fifth lens bands includes at least one non-spherical surface, and the fourth lens band includes more than two non-spherical surfaces.

Application No.: 09/988,793

Docket No.: R2180.0113/P113

65. (Previously Presented) The apparatus according to claim 56, wherein said third lens band includes one lens, and said aperture diaphragm is located at the object side of the third lens band.

66. (Previously Presented) The apparatus according to claim 44, wherein said first lens band is immobile.

67. (Previously Presented) The apparatus according to claim 44, wherein said third lens band and aperture diaphragm are immobile.

68. (Previously Presented) The apparatus according to claim 44, wherein the fifth lens band performs focusing.

69. (Previously Presented) The apparatus according to claim 44, wherein a focal length ( $f_1$ ) of the first lens band, and a composite focal length ( $f_{12T}$ ) of the first and second lens bands at the long focal point end substantially meet the following inequality:

$$-1.4 < (f_{12T} / f_1) < -1.0.$$

70. (Previously Presented) The apparatus according to claim 44, wherein a composite focal length ( $f_{12W}$ ) of the first and second lens bands at the short focal point end, a composite focal length ( $f_{12T}$ ) of the first and second lens bands at the long focal point end, a focal length ( $f_T$ ) of the entire lens unit at the long focal point end, and a focal length ( $f_W$ ) of the entire lens unit at the short focal point end substantially meet the following inequality:

$$0.4 < (f_{12T} / f_{12W}) / (f_T / f_W) < 0.7.$$

Application No.: 09/988,793

Docket No.: R2180.0113/P113

71. (Previously Presented) The apparatus according to claim 44, wherein each of said lens bands includes less than three lenses, said second and third lens bands include at least one non-spherical surface, and at least one of said fourth and fifth lens band includes more than one non-spherical surface.

72. (Previously Presented) The apparatus according to claim 44, wherein said first to third and fifth lens bands include less than three lenses, said fourth lens band includes four lenses, each of said second and third lens bands includes at least one non-spherical surface, and at least one of said fourth and fifth lens band includes more than one non-spherical surface.

73. (Previously Presented) The apparatus according to claim 44, wherein said fifth lens band includes only one lens.

74. (Previously Presented) The apparatus according to claim 44, wherein said aperture diaphragm is located at the object side of the third lens band.

75. (Previously Presented) The apparatus according to claim 44, further comprising a function of digitizing a photographed image into digital information.

76. (Previously Presented) The apparatus according to claim 75, further comprising a photo acceptance unit configured to receive an image from the zoom lens, said photo acceptance unit having almost three million pixels.

77. (Previously Presented) The apparatus claimed in claim 73, said zoom lens further comprising a macro mode capable of focusing at a shorter distance than an ordinal photographing region, wherein said focusing is performed by movement of the fifth lens band in a predetermined direction in any one of the ordinal photographing region and the macro mode.

Application No.: 09/988,793

Docket No.: R2180.0113/P113

78. (Previously Presented) The apparatus according to claim 77, wherein said fourth lens band in the macro mode is substantially close to the fourth lens band in the long focal point end arrangement.

79. (Previously Presented) The apparatus according to claim 77, wherein said second lens band in the macro mode is substantially closer to the image surface than when it is in the short focal point end arrangement.

80. (Previously Presented) The apparatus according to claim 77, wherein said fourth lens band in the macro mode is close to the fourth lens band in the long focal point end arrangement, and wherein said second lens band in the macro mode is closer to the imaging surface than when it is in the short focal point end arrangement.

81. (Previously Presented) The apparatus according to claim 77, wherein the first and third lens bands and the aperture diaphragm are immobile with regard to the image surface.

82. (Previously Presented) The apparatus according to claim 77, wherein a distance (L1W) between the first and second lens bands in the short focal point end arrangement, a distance (L1T) between the first and second lens bands in the long focal point end arrangement, a distance (L1C) between the first and second lens bands in the macro mode substantially meet the following inequality:

$$0.15 < (L1C - L1W) / (L1T - L1W) < 0.40.$$

83. (Previously Presented) The apparatus according to claim 77, wherein a distance (L3W) between the third and fourth lens bands in the short focal point end arrangement, a distance (L3T) between the third and fourth lens bands in the long focal

Application No.: 09/988,793

Docket No.: R2180.0113/P113

point end arrangement, a distance (L3C) between the third and fourth lens bands in the macro mode substantially meet the following inequality:

$$0.25 < (L3C - L3W) / (L3W - L3T) < 0.50.$$

84. (Previously Presented) The apparatus according to claim 77, wherein a distance (L1W) between the first and second lens bands in the short focal point end arrangement, a distance (L1T) between the first and second lens bands in the long focal point end arrangement, a distance (L1C) between the first and second lens bands in the macro mode substantially meet the following inequality:

$$0.15 < (L1C - L1W) / (L1T - L1W) < 0.40$$

and wherein a distance (L3W) between the third and fourth lens bands in the short focal point end arrangement, a distance (L3T) between the third and fourth lens bands in the long focal point end, a distance (L3C) between the third and fourth lens bands in the macro mode substantially meet the following inequality:

$$0.25 < (L3C - L3W) / (L3W - L3T) < 0.50.$$

85. (Previously Presented) The apparatus according to claim 77, wherein said first to third and fifth lens bands include less than three lenses, said fourth lens band includes four lenses, each of said second, third and fifth lens bands includes at least one non-spherical surface, and the fourth lens band includes more than two non-spherical surfaces.

86. (Previously Presented) The apparatus according to claim 77, wherein said third lens band includes one lens, and said aperture diaphragm is located at the object side of the third lens band.